



Advanced Repair Technology, Inc.

The Science of Repair

MATERIAL DATA SAFETY SHEET

Product: Advanced Repair Technology Flex-Tec HV® – Part B

MANUFACTURER'S NAME AND ADDRESS

Advanced Repair Technology, Inc.

PO Box 510 Cherry Valley, New York 13320
607.264.9040

EMERGENCY TELEPHONE

For Chemical Emergency Exposure, or Accident
Call CHEM TREC 800-424-9300 (24 hours)

SECTION I – PRODUCT IDENTIFICATION

Chemical Name:	Polyamine/Dimer Acid Polymer
Product/Trade Name:	Flex-Tec HV Epoxy Resin Compound Part B
Chemical Family:	Fatty Amine
Synonyms:	Epoxy Hardener
CAS Registry #1	Proprietary - A blend of several materials
Formula:	Proprietary

Hazard Designations	HMIS	NPFA
Health	2	1
Flammability	1	1
Reactivity	0	0
Protective Equipment or Special Hazards	0	0

0=Minimal 1=Slight 2=Moderate 3=Serious 4=Severe

SECTION II – HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Ingredients	Percent	TLV (Units)
Polyamide Resin	50-90	None established
Triethylene Tetramine	<10	None established

SECTION III – HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Boiling Point	N.A.
Freezing Point	N.A.
Melting Point	N.A.
Vapor Pressure	N.A.
Vapor Density	N.A.
Solubility in Water	Moderate
Specific Gravity	.97
% Volatility by Volume	< 1%
Evaporation Rate	Low
State	Liquid
Viscosity	Paste
Other Information	N.A.
Appearance & Odor	Yellow paste, slight ammonia odor

SECTION IV – FIRE & EXPLOSION HAZARD DATA

Flash point (Method used): Over 365° F. Open Cup.

Flammable Limits: Lower NA / Upper NA

Fire Extinguishing Media: To extinguish fires involving this material –use water spray, dry chemical, or carbon dioxide.

Special Fire Fighting Procedures: If not leaking, keep fire exposed containers cool with a water spray to prevent rupture due to excessive heat. High pressure water hose may spread product from broken containers increasing contamination or fire hazard. As in any fire, prevent human exposure to fire, smoke, fumes or products of combustion. Evacuate nonessential personnel from the area. Fire fighters should wear fullface, self contained breathing apparatus and impervious protective clothing. Use standard firefighting techniques.

VISIT US ON THE WEB!

WWW.ADVANCEDREPAIR.COM FOR TECH SUPPORT & HOW TO DEMOS



Advanced Repair Technology, Inc.

The Science of Repair

SECTION V – HEALTH HAZARD DATA

Threshold Limit Value: None established.

Health Hazards: WARNING! May cause irritation. Avoid contact with skin, eyes, and clothing. The principal routes of entry for this material are inhalation and skin absorption. Inhalation of the vapors may produce respiratory failure. Ingestion of the material may produce abdominal pain and diarrhea, depression, convulsion, and in serious cases, unconsciousness. This product is a skin and eye irritant. Dermatitis may result from prolonged or repeated skin contact.

Emergency & First Aid Procedures: call a physician immediately. If a known exposure occurs or is suspected, immediately initiated the recommended procedures below. Ingestion: if swallowed, immediately give several glasses of water, but do not induce vomiting. If vomiting occurs, give more fluid. Have a physician determine if condition of patient will permit evacuation of stomach, or induction of vomiting. Do not give fluid to an unconscious person.

Skin Contact: flush all affected areas with water for 15 minutes. Remove any contaminated clothing or shoes. Seek medical attention if skin irritation occurs. Wash or discard clothing.

Eye Contact: immediately flush the eye with large amounts of water for at least 15 minutes. Hold eyelids apart to assure a thorough flushing. Do not attempt to neutralize any chemical. Obtain medical assistance as soon as possible. Flush an additional 15 minutes if medical attention is not available. Inhalation: remove from area. Seek medical attention if breathing is difficult. Oxygen may be delivered upon a physician's advice. If not breathing, give artificial respiration, preferably mouth to mouth.

Toxicological Data: While none has been established, the material is corrosive, as it is a strong base. It can cause severe eye damage, or burns to the throat if swallowed. It may cause skin irritation.

SECTION VI – REACTIVITY DATA

Stability:	Stable
Condition to Avoid:	Strong oxidants, acids, high temperatures.
Incompatibility:	Acids, strong oxidants
Hazardous Combustion or Decomposition Products:	Carbon monoxide, Carbon dioxide, of nitrogen.
Hazardous Polymerization:	Will not occur

SECTION VII – SPILL, LEAK, AND WASTE DISPOSAL PROCEDURES

Waste Disposal and Spill Control Methods

Follow good industrial hygiene practices. (See sec. VIII). Anyone entering an area with high levels of vapor should use a self contained air pack. Small spills can be handled in a more routine manner. Use adequate ventilation and wear a respirator to prevent inhalation exposure. Wear protective clothing and splash goggles. Soak up liquid with a suitable absorbent, such as sawdust, clay, or oil absorber. Soak up absorbed material and place in a chemical waste drum for disposal. Wash up area with detergent and water, flush with water. Large spills should be diked and pumped into a drum for salvage or disposal. Material that cannot be used should be disposed of in an epa authorized facility. Dispose of empty containers according to any applicable regulations under the resource conservation and recovery act.

SECTION VIII – SPECIAL PROTECTION INFORMATION

Respiratory Protection: if use conditions generate vapor, the material should be handled in an open or well-ventilated area. Where adequate ventilation is not available, use niosh approved organic vapor respirators. Where exposure necessitates a higher level of protection, a positive pressure air supply respirator is recommended.

Ventilation: General mechanical ventilation recommended in closed area.

Personal Protection: Protective apron or coveralls. Splash goggles, and approved plastic or rubber gloves is suggested.

Work Practices/Hygiene: Use good hygienic practice

ADVANCED REPAIR TECHNOLOGY • P.O. Box 510 • Cherry Valley, NY 13320
 Phone: 607-264-9040 • Tech Support: 866-859-2787 • Fax: 607-264-8307
 Email: contactadvancedrepair@gmail.com

VISIT US ON THE WEB! WWW.ADVANCEDREPAIR.COM FOR TECH SUPPORT & HOW TO DEMOS



Advanced Repair Technology, Inc.

The Science of Repair

SECTION IX – SPECIAL PRECAUTIONS

Handling and Storage: Containers should be stored in a cool, dry, well ventilated area away from flammable materials and sources of heat or flame. Exercise caution to prevent damage to or leakage from the container.

Other Precautions: Non-corrosive to steel. Some plastics may swell under exposure to material.

Precautionary Labeling: Corrosive material. Strong base

SECTION X – ADDITIONAL INFORMATION

N.A.

SECTION XI – REQUIREMENTS OF TRANSPORTATION

Proper Ship Name:	Corrosive liquid N.O.S.
Hazard Name:	Polyamine
Hazard Class:	8
Label/Placard:	Corrosive
UN/NA #:	UN 1760
EPA RQ N:	.00 Pounds or .00 Kilos
Special Provisions:	None

May 2013

ADVANCED REPAIR TECHNOLOGY • P.O. Box 510 • Cherry Valley, NY 13320
Phone: 607-264-9040 • Tech Support: 866-859-2787 • Fax: 607-264-8307
Email: contactadvancedrepair@gmail.com

VISIT US ON THE WEB! WWW.ADVANCEDREPAIR.COM FOR TECH SUPPORT & HOW TO DEMOS